

Nitrogen Evaporator Comparison

Organomation MULTIVAP vs. Biotage TurboVap



	Organomation MULTIVAP (water bath models only)	Biotage TurboVap LV
Price Range	\$4k - \$9k	\$11k - \$14k
Sample Capacity	64 or 100 samples	24 or 48 samples
Flexibility	Can hold one tube size per rack	Can hold a range of tube sizes per rack, but only one at a time
Gas Flow Control	Independent gas control to each row	Independent gas control to each row
Nitrogen Consumption	33 L/min	160 L/min
Temperature Range	30 °C - 100 °C	Ambient to 90 °C
Safe With Corrosive Solvents?	Yes <i>(rated for use with up to 3M HCl)</i>	Yes <i>(rated for use with up to 0.1M HCl)</i>
Safe With Explosive Solvents?	Yes	Yes
Placement	In fume hood	In fume hood or attached to ventilation system
Warranty	1 year	1 year

The MULTIVAP and TurboVap are both highly popular nitrogen evaporators that are designed to concentrate down batches of test samples prior to analysis. Now that you've compared their main specifications, let's get into when each evaporator would be preferred.

Price - **MULTIVAP**

For labs that have a limited budget such as start-ups or academic labs who are restricted by grant funding, the MULTIVAP provides a much more affordable option than the TurboVap. Water bath MULTIVAP models start at around \$7k, but unheated models are also available starting at around \$4k. Even the highest capacity MULTIVAP with additional features is less than the base model TurboVap. The simplicity of Organamation's units allow the cost of both the unit itself and the overall maintenance to remain low.

Digital Features - **TurboVap**

Unlike the MULTIVAP which has a button-interfaced control box, the TurboVap includes a digital touch screen where you can control the heat and gas flow. The digital system allows you to save preferences and methods in the system for future use. Although entirely preference-based, the touch screen feature can provide a more modern approach to the evaporation process.



Corrosive Solvents - **MULTIVAP**

Although both units have an acid resistant version to prevent corrosion, the MULTIVAP is rated for a higher concentration of strong acids or bases such as hydrochloric acid, formic acid, or tetrahydrofuran. For comparison, the MULTIVAP is rated for concentrations of up to 3M of HCl while the TurboVap is only rated for concentrations of up to 0.1M HCl. If you'll be working with these types of corrosive solvents, the PTFE-coated MULTIVAP will provide a longer-lasting solution.

Test Tube Rack Flexibility - TurboVap

The TurboVap flexible sample racks are designed to hold a range of tube sizes to prevent a custom rack needed to be made, and to save storage space in your lab. The MULTIVAP sample racks, on the other hand, are customized to fit just one sample size, requiring you to purchase an additional rack for each additional tube size being used.

Capacity - MULTIVAP

For high throughput laboratories, the large capacity MULTIVAPs will be the better suited solution. The water bath MULTIVAPs allow you to evaporate either 64 or 100 samples at once, whereas the TurboVap can only hold up to 48. You may think that double the capacity means double the size, but the two units are actually quite similar. The footprint of the TurboVap is 15" x 15" while the MULTIVAP is only slightly bigger at 17" x 19".



Automation - TurboVap

For labs that require a more hands-off evaporation experience, the TurboVap will be the better solution. The TurboVap LV allows the gas flow to slowly increase throughout the evaporation cycle eliminating manual adjustments, and also includes an alarm that goes off once your samples have reached a specific volume.

The water bath MULTIVAPs include a timer function that can shut the heat and gas flow off after a specified amount of time. Although it is not based on solvent volume, the timer can be just as useful once you're familiar with your evaporation rates.

Nitrogen Consumption - **MULTIVAP**

The MULTIVAP requires much less nitrogen flow than the TurboVap making it the better option for labs who are looking to conserve their gas consumption. For comparison, the 48 position TurboVap requires 160 L/min of nitrogen while the 100 position MULTIVAP (double the capacity) only requires 33 L/min. Whether you're using nitrogen tanks or producing your own nitrogen with a generator, the minimal gas usage of the MULTIVAP provides a much more affordable and economical option.



Limited Fume Hood Space - **TurboVap**

The TurboVap models have the option to either be used within a fume hood, or to be connected to a ventilation system using an exhaust outlet at the back of the unit. If your lab has limited fume hood space or even no fume hood at all, the TurboVap allows you to use it on just a regular benchtop workspace.

The general recommendation is to always use the MULTIVAP within a fume hood, however a portable fume extractor can also be used in instances where that's not possible.



Tube Visibility - TurboVap

If it's important for you to keep an eye on your test tubes throughout the evaporation process, the TurboVap would be preferred. The TurboVap's water bath has a glass casing that allows your samples to remain visible as the solvent level goes down, which can be important when drying to a specific end-point or to complete dryness.



The MULTIVAP has an aluminum water bath, only allowing you to view your samples from the top. You can lift the rack out of the bath for quick visibility, but this requires you to remove them out of the heat source, possibly slowing down the evaporation process.

In Summary

MULTIVAP

- More affordable
- Less prone to solvent corrosion
- Higher capacity
- Less nitrogen needed

TurboVap

- More digital features
- Less test tube racks needed
- More automated system
- Can be used outside the fume hood
- Easier tube visibility